



*Testing conditions completed at 100°C in a hot box to more closely simulate real-world use.*

100°C	kW	kW	kW	kW	kW	kW
Alt RPM	130a-24v (tested at 26.6vdc)	130a-48v (tested at 53.2vdc)	160a-48v (tested at 53.2vdc)	185a-24v (tested at 27.4vdc)	255a-12v (tested at 13.7vdc)	360a-12v (tested at 13.7vdc)
1280	159.6					
1288					164.4	
1500	824.6					
1780						150.7
1800					1438.5	
1893				137		
2000	1862			438.4	1657.7	986.4
2475		319.2				
2500	2420.6	478.8		2082.4	2000.2	1986.5
3000	2713.2	2447.2		2822.2	2233.1	2534.5
3370		3511.2				
3390			319.2			
3500	2846.2	3830.4	798	3452.4	2424.9	2794.8
3590	2926					
4000	2952.6	4681.6	3138.8	3726.4	2520.8	3027.7
4500	2979.2	5160.4	4628.4	3973	2466	3109.9
5000	2979.2	5426.4	5426.4	4027.8	2548.2	3219.5
5500	3005.8	5426.4	6064.8	4164.8	2575.6	3288
6000	3005.8	5586	6596.8	4274.4	2603	3507.2
6500	3005.8	5692.4	6916	4356.6	2466	3603.1
7000	3005.8	5745.6	7182	4384	2466	3644.2
7500	3005.8	5745.6	7394.8	4438.8	2466	3685.3
8000	3005.8	5745.6	7554.4	4466.2	2493.4	3562
8500	3005.8	5745.6	7660.8	4521	2534.5	3616.8
9000	3005.8	5745.6	7660.8	4548.4	2479.7	3616.8